

DRIVEN TO OUTPERFORM.



UP TO

500

MAX FASTENING

TORQUE

2X MORE RUN-TIME 3X MOTOR DURABILITY UP TO

500

EBS

MAX FASTENING

TORQUE

UP TO

2X

MORE
RUN-TIME

UP TO

3X

MOTOR

DURABILITY





M18 FUEL™ 2765-22 VS COMPETITORS					
	Milwaukee [®]	Milwaukee [®]	Bosch	Makita	
	*	***	7	7	
	2765-22	2665-22	HTH182-01	LXWT01	
Motor	POWERSTATE™ Brushless	4-Pole Neo	Can	2-Pole Ferrite	
Max Fastening Torque	500 ftlbs.	350 ftlbs.	500 ftlbs.	300 ftlbs.	
Impacts Per Minute	0 – 2,300	0 – 2,200	0 – 2,100	0 – 2,200	
Length	9-1/4"	9-1/2"	10-3/4"	10-3/4"	
Drive-Control™	Yes	No	No	No	
LED Light	Yes	No	Yes	Yes	
Powered By	REDLITHIUM™ XC4.0	REDLITHIUM™	Li-ion	Li-ion	

PROPRIETARY 2-MODE DRIVE CONTROL™

2765	MODE 1	MODE 2
No Load Speed (RPM/IPM)	0 - 1,200 / 0 - 1,700	0 - 1,700 / 0 - 2,300
Max Fastening Torque	300 ftlbs.	500 ftlbs.

AVAILABLE ACCESSORIES

SHIP AUGER BITS	
48-13-5680	11/16" x 18"
48-13-5810	13/16" x 18"
48-13-5930	15/16" x 18"
48-13-6010	1-1/16" x 18"



M18 FUEL" 7/16" Hex Utility Impacting Drill (Tool-Only) 2765-20

Includes: 2765-20 M18 FUEL™ 7/16" Hex Utility Impacting Drill



M18 FUEL™ 7/16" Hex Utility Impacting Drill (Kit - 2 Batteries) 2765-22

2763-22
Includes: 2765-20 M18 FUEL™ 7/16" Hex Utility Impacting Drill, (2) M18™ REDLITHIUM™ XC4.0 Extended Capacity Battery Packs, M18™ AC/DC Charger, and Contractor Bag